

# Digital Real-Time™ Oscilloscopes

TDS 684C • TDS 680C • TDS 654C • TDS 620B • TDS 640A



## Features and Benefits


TDS 684C/TDS 680C/TDS 654C/TDS 620B/  
TDS 640A

- 1 GHz and 500 MHz Bandwidth Performance to Work with Fast Signals in Today's Digital Designs
- 5 GS/s Sample Rates\*
- Record Length to 15,000 Points
- 1 mV/div to 10 V/div Sensitivity
- 1.5% Vertical Accuracy
- Histograms and Measurement Statistics to More Fully Characterize Design Performance
- Support for Java Applications Packages
- Hard Disk Drive Storage (option)
- Support for External Zip Drive
- Waveform Math and Advanced Waveform DSP
- 1 ns Peak Detect (not available w/TDS640A)
- Channel Deskew (not available w/TDS640A)
- Fully Automated Measurement System
- Waveform Pass/Fail Template Testing
- Color Display (TDS654C, TDS684C)
- RS-232, Centronics, and GPIB



## Applications

- Digital Design and Characterization
- Telecommunications/Datacommunications
- Transient Event Capture
- High Energy Physics



### TDS 684C

Your designs may be digital but at today's speeds, many of your toughest problems aren't. Crosstalk noise. Transmission effects. Ground bounce. Not to mention sub-nanosecond edges. Today's design problems require high bandwidth oscilloscopes that can measure up to these challenges. The Digital Real-Time™ architecture of the TDS 600 Series simplifies capturing intermittent signals or non-recurring problems like glitches or metastable states caused by setup and hold time violations.

TDS 600 Series provides design engineers excellent single shot accuracy for multi-channel, high speed signal characterization. Additional features and specifications of the TDS 600 Series are explained in the TDS Reference section available at [http://www.tek.com/Measurement/Products/catalog/scopes/tds\\_series](http://www.tek.com/Measurement/Products/catalog/scopes/tds_series).

	TDS 640A	TDS 620B	TDS 654C	TDS 680C	TDS 684C
Total Channels	4	2 + 2	4	2 + 2	4
Sample Rate (all channels simultaneously)	2 GS/s	2.5 GS/s	5 GS/s	5 GS/s	5 GS/s
Real-time Bandwidth	500 MHz	500 MHz	500 MHz	1 GHz	1 GHz
Maximum Record Length per Channel	2,000 pts	15,000 pts	15,000 pts	15,000 pts	15,000 pts
Vertical Resolution	8-Bits; >11-Bits with averaging				
Time Measurement Accuracy	<110 ps @ 2 GS/s	<100 ps @ 2.5 GS/s	<50 ps @ 5 GS/s	<50 ps @ 5 GS/s	<50 ps @ 5 GS/s
Advanced Waveform DSP/Math	Std.	Std.	Std.	Std.	Std.
Histograms and Measurement Statistics	N/A	N/A	Std.	Std.	Std.
Standard Probes	4 P6139A	2 P6139A	4 P6243	None	None
Display Type	7 in. mono	7 in. mono	7 in. color	7 in. mono	7 in. color
Floppy Drive	Std.	Std.	Std.	Std.	Std.
GPIB Port	Std.	Std.	Std.	Std.	Std.
RS-232 & Centronics	Std.	Std.	Std.	Std.	Std.
VGA I/O Port	Std. Mono	Std. Mono	Std. Color	Std. Mono	Std. Color
Printer Ports					
Hard Disk Drive	N/A	N/A	Opt.	Opt.	Opt.

\* Not available with TDS620B or TDS640A



See Tektronix on the World Wide Web:  
<http://www.tek.com>



Tektronix measurement products are manufactured in ISO registered facilities.



Product(s) complies with IEEE Standard 488.2-1987, and with Tektronix Standard Codes and Formats.

### TIME BASE SYSTEM

**Time Bases** – Main and Delayed.

**Time/div Range** – 200 ps/div to 10 s/div.  
Except TDS 640A: 500 ps/div to 5 s/div.

**Time Base Accuracy** – Over Any Interval  
>1ms ±100 ppm.

**Record Length per Channel** – 500 to 15,000 pts. Except TDS 640A: 500 to 2,000 pts.

**Pre-Trigger Position** – 0% to 100% of Record.

### VERTICAL SYSTEM

**Vertical Resolution** – 8-Bits (>11-Bits with averaging).

**Vertical Sensitivity** – 1 mV/div to 10 V/div.

**Maximum Input Voltage** – 300 V CAT II; ±400 V peak. Derate at 20 dB/decade above 1 MHz.

**DC Gain Accuracy** – 1.50%.

**Position Range** – ±5 divs.

**Offset** – Primary channels: ±1 V from 1 to 99.5 mV/div, ±10 V from 100 mV to

# Digital Real-Time™ Oscilloscopes

TDS 684C • TDS 680C • TDS 654C • TDS 620B • TDS 640A

## CHARACTERISTICS

995 mV/div,  $\pm 100$  V from 1 V to 10 V/div.  
Aux. 1, Aux. 2 (TDS 620B, TDS 680C only):  
same as primary channels.

**Bandwidth Selections** – 20 MHz, 250 MHz,  
and Full.

**Input Impedance Selections** – 1 M $\Omega$  in paral-  
lel with 10 pF, or 50  $\Omega$  (AC and DC coupling).

**Input Coupling** – AC, DC or GND.

**AC Coupled Low Frequency Limit** – <10 Hz  
when AC, 1 M $\Omega$  coupled. <200 kHz when AC,  
50  $\Omega$  coupled.

**Channel Isolation** – >100:1 at 100 MHz and  
>30:1 at BW for any two channels having  
equal V/div settings.

### ACQUISITION MODES

Peak Detect\*<sup>1</sup>, Sample, Single Sequence,  
Envelope, Average.

### TRIGGERING SYSTEM

**Triggers** – Edge (main and delayed); Pulse

(Width, Glitch, Runt, Slew Rate\*<sup>1</sup>, Time Out\*<sup>1</sup>);  
Logic (Pattern, State, and Setup & Hold Time  
Violation\*<sup>1</sup>); HDTV Video (optional).

**Main Trigger Modes** – Auto, Normal, Single.

**Delayed Trigger** – Delay by time, events, or  
events and time.

**Delay by Time Range** – 16 ns to 250 s. Except  
TDS 640A: 16 ns to 250 s for t/div setting <10  
 $\mu$ s; 15.1 to 250 s for t/div setting >25  $\mu$ s.

**Delay by Events Range** – 1 to 9,999,999 events.

**External Trigger Input** – Input Impedance:  $\geq 1.5$   
k $\Omega$ ; Max. Input Voltage:  $\pm 20$  V (DC + peak AC).

### DISPLAY

**Color CRT Monitor (TDS 654C/684C)** – 7 in.  
diagonal NuColor™ liquid crystal full-color  
shutter, 256 levels.

**Monochrome CRT Monitor (TDS 620B/680C/  
640A)** – 7 in. diagonal, magnetic deflection.  
Horizontal raster-scan. P4 white phosphor.

### MEASUREMENT SYSTEM

**Automatic Measurements** – 25 (on entire  
record or gated region).

**Measurement Accuracy** – TDS  
654C/680C/684C: <50 ps typical @ 5 GS/s  
single shot; TDS 620B: <100 ps typical @ 2.5  
GS/s single shot. TDS 640A: <110 ps @ 2  
GS/s single shot.

**Cursors Measurement** – Absolute, Delta;  
volts, time, frequency, NTSC IRE units and  
line number with Video Trigger Option.

### WAVEFORM PROCESSING

**Waveform Functions** – Interpolation (sin(x)/x  
or linear), Average, Envelope, Auto Setup.

**Advanced Waveform Functions** – FFT,  
Integration, Differentiation, Waveform (math  
or acquired) Limit Testing.

\*<sup>1</sup> Not available in TDS 640A

## ORDERING INFORMATION

### TDS 684C

Four-channel Color 1 GHz, 5 GS/s Per Channel  
Digital Real-Time Oscilloscope.

### TDS 680C

Two-channel Monochrome 1 GHz, 5 GS/s Per  
Channel Digital Real-Time Oscilloscope.

### TDS 654C

Four-channel Color 500 MHz, 5 GS/s Per Channel  
Digital Real-Time Oscilloscope. **Includes:** four  
P6243 FET Probes.

### TDS 684C, TDS 680C, TDS 654C INCLUDE

User Manual (070-0130-00); User Supplement (071-  
0273-00); Quick Reference Guide (020-2235-00);  
Programmer's Manual in MS-Help format on floppy  
disk (063-3120-00); Technical Reference Manual  
(071-0272-00).

### TDS 640A

Four-channel Monochrome 500 MHz, 2.0 GS/s Per  
Channel Digital Real-Time Oscilloscope.

**Includes:** Four P6139A Passive Probes. User  
Manual (070-8715-04); Quick Reference Guide  
(070-8711-02); Programmer's Manual in MS-Help  
format on floppy disk (070-8709-07); Technical  
Reference Manual (070-8717-02).

### TDS 620B

Two-channel Monochrome 500 MHz, 2.5 GS/s Per  
Channel Digital Real-Time Oscilloscope.

**Includes:** Two P6139A Passive Probes. User  
Manual (071-0130-00); Quick Reference Guide  
(020-2235-00); Programmer's Manual in MS-Help  
format on floppy disk (063-3002-00); Technical  
Reference Manual (071-0135-00).

### ALL INCLUDE

Front Cover (200-3696-00); North American Power  
Cord (161-0230-01); Accessory Pouch (TDS  
654C/TDS 684C Only) 016-1268-00.

### OPTIONS AVAILABLE (EXCEPT WHERE NOTED)

**Opt. 05** – Video Trigger, NTSC, PAL, HDTV,  
FlexFormat™.

**Opt. 1K** – Model K420 Instrument Cart.

**Opt. 1R** – Rackmount Kit.

**Opt. 2D** – (TDS 620B only) Delete Standard two  
P6139A Probes.

**Opt 33** – (TDS684C/TDS680C only) Add 1 ea.  
P6158 Low Capacitance Probe.

**Opt 34** – (TDS684C/680C/654C Only) Add 1 ea.  
P6247 differential Probe.

**Opt 35** – (TDS654C Only) Add 1 ea. P6243 Active  
Probe.

**Opt 36** – (TDS684C/680C/654C Only) Add 1ea.  
P6139A Passive Probe.

**Opt 37** – (TDS684C/680C Only) add 1 ea. P6245  
Active Probe.

**Opt HD** – (TDS684C/680C/654C Only) Internal Hard  
Disk Drive.

**Opt. D1** – Calibration Data Report.

### INTERNATIONAL POWER PLUG OPTIONS

**Opt. A1** – Universal Euro 220 V, 50 Hz.

**Opt. A2** – UK 240 V, 50 Hz.

**Opt. A3** – Australian 240 V, 50 Hz.

**Opt. A4** – North American 240 V, 60 Hz.

**Opt. A5** – Switzerland 220 V, 50 Hz.

### MEASUREMENT SERVICE OPTIONS

**Opt. C3** – Three years of Calibration Services.

**Opt. C5** – Five years of Calibration Services.

**Opt. D3** – Test Data (requires Opt. C3).

**Opt. D5** – Test Data (requires Opt. C5).

**Opt. R5** – Repair warranty extended to cover five  
years.

### RECOMMENDED ACCESSORIES

**WSTRO** – WaveStar™ software for Oscilloscopes,  
Windows 95/NT application for waveform capture,  
analysis, documentation and control from your PC.

**P6563A** – 500 MHz, 20X SMD Probe

**SureFoot** – Surface Mount Device Interconnects.

### For further information, contact Tektronix:

World Wide Web: <http://www.tek.com>; ASEAN Countries (65) 356-3900; Australia & New Zealand 61 (2) 888-7066; Austria, Eastern Europe, & Middle East +43 2236 8092 0; Belgium +32 (2) 715.89.70;  
Brazil and South America 55 (11) 3741-8360; Canada 1 (800) 661-5625; Denmark +45 (44) 850 700; Finland +358 (9) 4783 400; France & North Africa +33 1 69 86 81 81; Germany + 49 (221) 94 77 400;  
Hong Kong (852) 2585-6688; India (91) 80-2275577; Italy +39 (2) 25086 501; Japan (Sony/Tektronix Corporation) 81 (3) 3448-3111; Mexico, Central America, & Caribbean 52 (5) 666-6333;  
The Netherlands +31 23 56 95555; Norway +47 22 07 07 00; People's Republic of China 86 (10) 6235 1230; Republic of Korea 82 (2) 528-5299; South Africa (27 11)651-5222; Spain & Portugal +34 (1) 372 6000;  
Sweden +46 (8) 629 6503; Switzerland +41 (41) 729 36 40; Taiwan 886 (2) 2722-9622; United Kingdom & Eire +44(0)1628 403400; USA 1 (800) 426-2200.

From other areas, contact: Tektronix, Inc. Export Sales, P.O. Box 500, M/S 50-255, Beaverton, Oregon 97077-0001, USA 1 (503) 627-6877.

Copyright © 1998, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

8/98 HB/XBS 55W-10066-6



2 • TDS 600 Series

**Tektronix**